

# STEIN-Diaphragm-wall-grab K 810 II HD





for the wall thickness 800 / 1000 / 1200 mm

with wire-rope-pulleys  $\varnothing$  800 mm for wire-rope  $\varnothing$  34 - 36 mm  
two double sheaves and one single sheave

The diaphragm wall grab is low in maintenance and is subjected to the safety regulation VCB 9a for handling of loads.

The cutting edges of the grab jaws are made of Hardox steel 450 and were especially hardened. Easy mounting of the grab jaws for excavation widths 800/1000/1200 mm. All the grab teeth as well as all the wire rope pulleys are quickly exchangeable due to their construction as ready to use components.

Paintwork: aluminium coloured rust protection coating.



## MFS Maschinenfabrik GmbH & Co KG

### Production

Phone + 49 (0) 4421 1434 0  
 Fax + 49 (0) 4421 3034 81  
 E-mail info@mfs-mafa.de  
 Address Langeoogstr. 13  
 26384 Wilhelmshaven | Germany

### Sale

Phone + 49 (0) 2323 9266 0  
 Fax + 49 (0) 2323 9266 25  
 E-mail kendlik@stein-ht.de  
 Address Schnittstr. 6  
 44653 Herne | Germany

Grab - body [kg]	17.700					
Extension 800 - 1000 mm [kg]	3.800					
Light extension 800 - 1000 mm [kg]	1.050					
Light extension 800 - 1200 mm [kg]	2.000					
Jaws opening [mm]	2800			3400		
Jaws width [mm]	800	1000	1200	800	1000	1200
Jaws weight [kg]	2.400	3.000	3.800	2.900	3.300	4.200
Overall weights minimal [kg]	20.100	21.750	23.500	22.250	23.000	23.900
Overall weights maximal [kg]	23.900	25.500	27.300	24.400	26.800	27.700

Documentation: technical specification, instruction sheet, maintenance manual, sheaving diagram, spare-parts list, safety instructions.